Page.

FIGURE 7. Curves showing effects of temperature and pressure on proportions of illuminants in oil-gas cracking process..... 35
8. Vapor-pressure curve for water..... 50
9. Experimental furnace used in laboratory for cracking oils in vapor phase, arranged for operating at atmosphere or diminished pressure. 54
10. Details of pressure connections of apparatus shown in figure 9..... 55
11. Curves representing average results of cracking four oils, showing influence of varying temperatures and pressures on quantity of oil recovered on basis of original oil..... 67
12. Curves showing percentages of oil recovered from cracking four oils under varying pressures at 500° C..... 67
13. Curves showing percentages of oil recovered from cracking four oils under varying pressures at 600° C..... 68
14. Curves showing percentages of oil recovered from cracking three oils under varying pressures at 750° C..... 69
15. Curves showing percentages of carbon formed from cracking four oils under varying pressures at 500° C..... 71
16. Curves showing percentages of carbon formed from cracking four oils under varying pressures at 600° C..... 71
17. Curves showing percentages of carbon formed from cracking three oils under varying pressures at 750° C..... 72
18. Curves representing average results of cracking four oils, showing variations in carbon formation with variations in temperature and pressure..... 72
19. Curves showing specific gravities of oils recovered from cracking oils under varying pressures at 500° C..... 75
20. Curves showing specific gravities of oils recovered from cracking oils under varying pressures at 600° C..... 75
21. Curves showing specific gravities of oils recovered from cracking oils under varying pressures at 750° C..... 76
22. Curves representing average results of cracking oils, and influence of varying temperatures and pressures on specific gravities of oils recovered..... 76
23. Curves showing percentages of gas formed from cracking a Pennsylvania refined burning oil with varying temperatures and pressures..... 80
24. Curves showing percentages of gas formed from cracking Oklahoma fuel-oil residuum with varying temperatures and pressures..... 82
25. Curves showing percentages of gas formed from cracking a California (Kern River) crude oil with varying temperatures and pressures... 82
26. Curves representing average results of cracking oils, showing influence of varying temperatures and pressures on formation of gasoline..... 85
27. Curves showing percentages of gasoline formed from cracking four oils under varying pressures at 500° C..... 85
28. Curves showing percentages of gasoline formed from cracking four oils under varying pressures at 600° C..... 86
29. Curves showing percentages of gasoline formed from cracking three oils under varying pressures at 750° C..... 87
30. Curves showing agreement of estimated percentages of benzene in cracked-oil distillates by the nitration and by the specific-gravity methods..... 93

Page.

FIGURE 31. Curves showing percentages of combined aromatic hydrocarbons formed from cracking three oils under varying pressures at 500° C. 97
32. Curves showing percentages of combined aromatic hydrocarbons formed from cracking three oils under varying pressures at 600° C. 97
33. Curves showing percentages of combined aromatic hydrocarbons formed from cracking three oils under varying pressures at 750° C. 97
34. Curves representing average results of cracking oils, showing influence of varying temperatures and pressures on formation of combined aromatic hydrocarbons..... 98
35. Curves showing varying amounts of five aromatic hydrocarbons recovered in cracked oils of various specific gravities..... 124
36. Curves showing effect of varying temperatures on formation of benzene and toluene when original oil is cracked in 6-inch by 10-foot tube, with constant rate of feed of 17 gallons per hour, and at a constant pressure of 250 pounds per square inch..... 138
37. Curves showing effect of varying rates of feed on formation of benzene and toluene, as well as on yield of recovered oil, when original oil is cracked in an 8-inch by 10-foot tube, at a constant temperature of 700° C. and a constant pressure of 250 pounds per square inch..... 144
38. Curves showing effect of varying temperatures on formation of benzene and toluene when an Oklahoma crude oil is cracked in 8-inch by 10-foot tube at a constant rate of feed of 22 gallons per hour and a constant pressure of 250 pounds per square inch..... 145
39. Cross section of tubes in 10-tube furnace..... 155
40. Plan and elevation of furnace at development plant..... 167
41. Cross section of furnace at development plant..... 168
42. Arrangement of stacks of 10-tube furnaces..... 169
43. Diagram of furnace connections..... 170
44. Details of stirring-rod drive and tar neck..... 174
45. Details of condenser construction..... 179